



Series 9500 Marine Intercom System

Headset-Mic
 Model No. H9530
 (Part No. 40864G-02)



H9530: Headset-Mic

FEATURES AND BENEFITS

- Dual-ear, over-the-head style
- Crisp, clear communication in demanding environments
- All hardware marine-grade stainless steel for rust/corrosion resistance in harsh marine environments
- M-87 type dynamic noise-canceling microphone, immersion-proof
- Hinged wire microphone boom, 280° rotational, for perfect microphone positioning on left- or right-side
- Dual dynamic earphones with stainless steel retainers offer exceptional intercom/radio reception
- 30' straight cord with 5-pole (green) quick-disconnect connector, mates to U9510BS Belt Station which provides mic control and headset volume control
- Undercut, comfort-gel ear seals provide unsurpassed comfort and enhanced noise-attenuation
- 4-chamber, air-flow pillow headpad affords long-term comfort, eliminates “hot-spots”
- Passive noise attenuation rating of 23 dB

DESCRIPTION

The Series 9500 Marine Intercom System is an ideal intercom/radio communications solution for the demanding marine environment. Our Series 9500 provides a reliable and effective solution for the high-noise environments of “workboats”, including law enforcement/homeland security, special operations and fire/rescue boat applications.

The H9530 is a marine-grade version of our legacy noise-attenuating headsets, providing the same rugged dependability but designed for use with David Clark U9510BS Belt Stations.

It is a dual-ear, over-the-head style communication headset incorporating a noise-canceling dynamic microphone which is optimal for extreme noise environments, effectively mitigating wind and engine noise.

With superlative performance and unsurpassed comfort features allowing for ease of use over long work shifts, the H9530 is an ideal headset choice for use where high noise levels make it difficult to communicate and effective hearing protection is desired.

TECHNICAL DATA

| | |
|---|--|
| Weight | 15.2oz/431g |
| Comm Cord | 30' Straight cord, quick-disconnect 5-pole (green) |
| Certified NRR (3rd party) | 23 dB |
| Dome Type | Lightweight, ABS |
| Hardware | Stainless-steel, EM Coat 6226 |
| Ear Impedance | 300Ω +/- 20% @ 1kHz |
| Ear Sensitivity | 105 dB min. SPL @ 1KHz re: 1mW RMS |
| Ear Freq. Response | 200-5,500 Hz |
| Mic Impedance | 5Ω +/- 20% @ 1kHz |
| Mic Sensitivity | 1.8 to 4.0 mV across 5Ω load; 74 dB SPL |
| Mic Freq. Response | 200- 6KHz, +/- 10 dB |
| Mic Distortion | <6% @ 114 dB SPL / 200-6KHz |

360 Franklin Street, Box 15054, Worcester, MA 01615-0054 • Tel: 800-298-6235 • Fax: 508-753-5827
 • Email: sales@davidclark.com • Web site: www.davidclark.com